**Aspentech Disclaimer

"Aspented biscalarer Aspen Techlogy may provide information regarding possible future product developments including new products, product features, product interfaces, integration, design, architecture, etc. that may be represented as "product roadmaps or product visions." Any such information is for discussion purposes only and does t constitute a commitment by Aspen Techlogy to do or deliver anything in these product roadmaps or otherwise. Any such commitment must be explicitly set forth in a written contract between the customer and Aspen Techlogy, executed by an authorized officer of each company

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Operating Systems (64-bit only)											
Windows 11	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Windows 10 Anniversary Enterprise & Professional (64-bit)	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark	\checkmark
Windows Server 2022	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark				
Windows Server 2019	\checkmark	\checkmark	\checkmark	\checkmark		\checkmark	\checkmark		\checkmark	\checkmark	
Windows Server 2016											
Ubuntu Server Edition 20.04 LTS											
Ubuntu Server Edition 18.04 LTS											
Ubuntu Server Edition 16.04 LTS											
RedHat Enterprise Linux 8.4+	\checkmark	\checkmark	\checkmark	\checkmark			\checkmark	\checkmark			
RedHat Enterprise Linux 7.6+	\checkmark	\checkmark	\checkmark	\checkmark			\checkmark	\checkmark	\checkmark		
Microsoft Office				-							
Office 365 (Desktop/Click-to-run) (32-bit/64-bit)										\checkmark	
Office 2021 (64-bit)											
Office 2021 (32-bit)											
Office 2019 (64-bit)											
Office 2019 (32-bit)											
Office 2016 (64-bit)											

Suite						SSE					
				Subsur	face Scie	nce & Eng	Jineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Office 2016 (32-bit)											
Office 2013 (32-bit)										\checkmark	
Database Servers											
Microsoft SQL Server 2022 (Enterprise/Standard Edition)											
Microsoft SQL Server 2022 (Express Edition)											
Microsoft SQL Server 2019 (Enterprise/Standard Edition)											
Microsoft SQL Server 2019 (Express Edition)											
Microsoft SQL Server 2017 (Enterprise/Standard Edition)											
Microsoft SQL Server 2017 (Express Edition)											
Microsoft SQL Server 2016 (Enterprise/Standard Edition)											
Microsoft SQL Server 2016 (Express Edition)											
Microsoft SQL Server 2014 (Enterprise/Standard Edition)											
Microsoft SQL Server 2014 (Express Edition)										\checkmark	
SQL Server 2022 Local DB											
SQL Server 2014 -2019 Analysis Services											
ProgresSQL 13.2											
Oracle Database 19.x.x 64-bit											
Database Clients											
Oracle Client 19.x 32-bit											
Oracle Client 19.x 64-bit											
Oracle Client 18.x 32-bit											

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Runtimes											
.NET Framework 4.8			\checkmark						\checkmark		
.NET Framework 4.6											
.NET 6.0.3			\checkmark								
Aspen AloT Cloud libraries											
ASP.NET Core 6.0.3											
64-bit Oracle Java 17 JDK LTS		~									
64-bit Oracle Java 17 JDK LTS		\checkmark									
64-bit Oracle Java 11 JDK LTS											
64-bit Oracle Java 8 JDK LTS											
64-bit Oracle Java 8 JDK LTS											
32-bit AdoptOpenJDK Java 17 JRE LTS											
64-bit AdoptOpenJDK Java 17 JRE LTS											
32-bit AdoptOpenJDK Java 11 JRE LTS											
64-bit AdoptOpenJDK Java 11 JRE LTS								\checkmark			
64-bit AdoptOpenJDK Java 8 JRE LTS											
Python		\checkmark		\checkmark			\checkmark	\checkmark		\checkmark	
MSXML 6											
Visual Studio 2022											
Visual Studio 2019	✓	\checkmark	\checkmark	\checkmark			\checkmark				
Visual Studio 2017						\checkmark					

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Visual Studio 2015									 ✓ 	\checkmark	
Visual Studio 2010 Tools for Office Runtime											
Microsoft Visual C++ Redistributable 2022											
Microsoft Visual C++ Redistributable 2019	\checkmark	\checkmark	\checkmark	\checkmark			\checkmark				
Microsoft Visual C++ Redistributable 2017							\checkmark				
Microsoft Visual C++ Redistributable 2015							\checkmark		\checkmark	\checkmark	
Microsoft Visual C++ Redistributable 2013				\checkmark						\checkmark	
Virtualization											
Microsoft Hyper-V (Server)											
VMware ESXi Hypervisor Server 6.x (Server)											
VMWare vSphere Enterprise Plus											
Microsoft Terminal Services (Desktop)											
Citrix Virtual Apps and Desktops 7.1912 (Desktop)											
Web Browsers											
Microsoft Edge	\checkmark	\checkmark					\checkmark			\checkmark	
Google Chrome Evergreen Version 75+	\checkmark	\checkmark					\checkmark			\checkmark	
Firefox	\checkmark	\checkmark					\checkmark			\checkmark	
Chrome on iOS 14+ for iPad Support										\checkmark	
Safari on iOS 14+ for iPad Support										\checkmark	
Android 10+										\checkmark	
Security Components/Services											
Aspen Framework (AFW) 5											

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
TLS 1.2	\checkmark	\checkmark	\checkmark				\checkmark				
Java App (Servers)											
Apache Tomcat 9.x											
Native Web Servers											
IIS 10											
Reporting Services											
Microsoft Report Viewer 2015											
Microsoft SQL Server 2014/2016/2017/2019/2020/2022 Reporting Services											
Load Balancing											
F5 Load Balancing											
Integration Components											
Aspen Supply Chain Connect											
Informatica Powercenter 10.5.2											
Cloud Support *											
Azure VM - Microsoft	\checkmark	\checkmark	\checkmark								\checkmark
Amazon VM (AWS)	\checkmark	\checkmark	\checkmark								
Azure VM - Linux	\checkmark	\checkmark	\checkmark								
Nutanix XiFrame											
Azure Virtual Desktop (AVD)											
AWS RDS (SQL)											
Azure SQL											
Deployment Tools											

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
sccм											
Supported Versions of Fortran											
FORTRAN 2021											
Desktop Types - Minimum Recommended											
Type I: Computer & processor: Intel Core-i5 family or faster Memory (RAM in GB): 16 Hard Disk (GB): 120 Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100					\checkmark	\checkmark				\checkmark	\checkmark
Type II: Computer & processor: Intel Core-i5 family or faster Memory (RAM in GB): 16 Hard Disk (GB): 250 Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100					V					\checkmark	\checkmark
Type III: Computer & processor: 4CPU >= 2.8GHz (turbo max 3.2 preferred) Memory (RAM in GB): 16 Hard Disk (GB): 100 Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100					\checkmark					\checkmark	\checkmark
Type IV: 2 x Intel Xeon 3.9GHz 8-core Memory (RAM in GB): 64GB Hard Disk (GB): 356 GB SSD Graphics Card: NVIDIA RTX A6000 GPU Monitor: 2 x 27" UHD monitors Network (MB/s): 100Mbps Server Types - Minimum Recommended		\checkmark		\checkmark			\checkmark	\checkmark			

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Type I: Computer & processor: Intel Core-i7 family or faster for standalone deployment Intel Xeon Gold series, 4 cores or more for multi-user environment Memory (RAM in GB): 16 + for standalone deployment, 32+ for multi-user environment Hard Disk (GB): 150 for standalone deployment, 300 for multi-user environment Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100											
Type II: Computer & processor: Intel Xeon Gold series type system (4 cores) or faster Memory (RAM in GB): 16 + Hard Disk (GB): 300 + Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100 (GB network recommended)											
Type III: Computer & processor: Intel Cascade Lake-based Xeon processor with 8 cores or more per processor Memory (RAM in GB): 32 or above gigabytes (GB) RAM Hard Disk (GB): 500 gigabytes (GB) or more available Monitor: Graphics hardware acceleration requires a DirectX10 graphics card and a 1440 x 900 or higher resolution monitor Network (MB/s): 100Mpbs (Gigabyte network recommended)											
Type IV: (IIoT Gateways) Computer & processor: ARM or Intel based CPU or more Memory (RAM in GB): 256Mb or more Hard Disk (GB): 128Mb or more											
Type V Windows Server 2019 v1809+ Memory (RAM in GB): Minimum: 16 Recommended: 32 Cores: Minimum: 4 , Recommended: 8 Disk space (GB): Minimum: 64, Recommended: 100 Network (MB/s): Minimum: 50, Recommended: 100											
Type VI Computer & processor: Intel Xeon E class processor or equivalent with dual core min. Memory (RAM in GB): Minimum: 4 Hard Disk (GB): Minimum 50. High IOPS drive, SSD preferred Network (MB/s): 100											
Type VII Computer & processor: Intel Xeon E class processor or equivalent with dual core min. Memory (RAM in GB): 8 + Hard Disk (GB): 100 GB min. High IOPS drive, SSD preferred Network (MB/s): 100Mpbs											

Suite						SSE					
				Subsur	face Scie	nce & Eng	gineering	(SSE)			
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill
Type VIII Computer & processor: Intel Xeon E class processor or equivalent with 8 cores or higher Memory (RAM in GB): 12 or above gigabytes (GB) RAM Hard Disk (GB): 2000 min. High IOPS drive, SSD preferred Network (MB/s): 200											
Type IX Single model engironment: Computer & processor: 4 vCPU >+ 2.8 GHz Memory (RAM in GB): 8+ Hard Disk (GB): 100 Network (MB/s): 100											
Type X Single model engironment: Computer & processor: 8 vCPU >+ 3.2 GHz Memory (RAM in GB): 16+ Hard Disk (GB): 100											
Type XI Multiple models within single environment (max models <= 10): Computer & processor: 4 vCPU >+ 2.8 GHz (add 1.5vCPU per concurrent user) Memory (RAM in GB): 8+ (add 3GB per concurrent user) Hard Disk (GB): 100 (add .5GB per concurrent user) Network (MB/s): 100											
Type XII Multiple models within single environment (max models <= 10): Computer & processor: 8 vCPU >+ 3.2 GHz (add 1.5vCPU per concurrent user) Memory (RAM in GB): 16 or above gigabytes (GB) RAM (add 4GB RAM per concurrent user) Hard Disk (GB): 100 GB min. (add .5GB per concurrent user) Network (MB/s): 100Mpbs											
Type XIII Supports 20 concurrent users: Computer & processor: 16 vCPU >+ 2.2 GHz) Memory (RAM in GB): 64 Hard Disk: 100 Network (MB/s) :10											
Type X1V Supports 100 concurrent users: Computer & processor: 16 vCPU >+ 2.2 GHz) Memory (RAM in GB): 32 Hard Disk (GB): 100 Network (MB/s): 5											

Suite	SSE													
				Subsur	face Scie	nce & Eng	gineering	(SSE)						
V14 Platform Specifications that are supported	Aspen Epos Services	Aspen Epos Application	Aspen Geolog Standalone	Aspen SKUA Standalone	Aspen OpsLink	Aspen Interpret	Aspen RMS	Aspen Tempest	Aspen METTE	Aspen Resview	Aspen Sysdrill			
Type XV Computer & processor; 16 vCPU >+ 2.2 GHz) Memory (RAM in GB); 32 Hard Disk (GB); 100														
* In general, AspenTech aspeNE® software license agreements with customers permit use of the licensed software on Supported Computers at customer Sites. "Supported Computers" include computers with a manufacture, model and operating system for which AspenTech offers a supported version of the software, and that are controlled by the customer. "Sites" are customer facilities or locations specified in the license agreement. AspenTech permits customer use of licensed aspeNE software in the cloud where: (i) the Platform Support specifications published by AspenTech for the relevant version of the software product include cloud support; (ii) only the customer has access to the licensed software hosted by the cloud service provider; and (iii) the user is accessing the software only from a Site specified in the applicable license agreement. Cloud deployment does t change any license restrictions, including the restrictions on which regions can access the software.														
When running software on a virtual machine, the machine should meet the same requirements. AspenTech does t support the in-place upgrade of the Operating System (for example: upgrade Windows 7 to Windows 10) with AspenTech software already installed. Our recommendation is to uninstall Aspen Software before upgrading the OS and reinstall it after the upgrade.														
Your Aspen SLM Server must be installed and running prior to installing any V14 product. If running standalone, 1280 x 800 is the minimum recommended resolution monitor for servers. For SLM server using Type 1 Desktop configuration, the minimum memory is 4GB with 20GB hard drive.														
Microsoft Active Directory/Domain Services (Required for aspeNE Web Server) A minimum of 10GB of free space is needed to install/upgrade products on the C drive. 1														
2/6/2023														